



產品特點：

- 1 產品在模具內部安裝，避免與模具外部零件及水路沖突；
- 2 具有內鎖模扣、二次頂出、複位機構的功能；
- 3 重要零件採用SKD11材質，使用時良好的潤滑性，更耐磨、壽命更長

D1	H max.	D5	L7	D2	D3	D4	D6	D7	D8	D5
32	28	14	63	M10	34.8	44.8	32.2	18.5	M24x1	14
			80							
			100							
	125									
	63									
	80									
38	36	18	100	M12	40.8	51.8	38.2	23.5	M30x1.5	16
			125							
			140							
	80									
	100									
	125									
71			140							

Code	L1	L2	L3	L4	L5	L6	Sw1
Z173-32x28x14x63	78	60	14	20	56	25	12
Z173-32x28x14x80					73		
Z173-32x28x14x100					93		
Z173-32x28x14x125					118		
Z173-32x56x14x63	106	88	14	20	73	25	12
Z173-32x56x14x80					93		
Z173-32x56x14x100					118		
Z173-32x56x14x125					133		
Z173-32x36x18x63	90	70	16	22	56	30	15
Z173-32x36x18x80					73		
Z173-32x36x18x100					93		
Z173-32x36x18x125					118		
Z173-32x71x18x63	126	105	16	22	73	30	15
Z173-32x71x18x80					93		
Z173-32x71x18x100					118		
Z173-32x71x18x125					133		